

AA800 Series – Power Amplifiers


The perfect high-performance Power Amplifiers for mid-sized locations.

Specifications:

MODEL		AA806	AA812	AA824
Power Requirements		230V AC, 50Hz		
Rated Output		60W	120W	240W
Distortion		Less than 2% at 1kHz		
Frequency Response		50-20000Hz (± 3 dB)		
Tone Control		Bass: ± 6 dB at 100Hz/Treble: ± 6 dB at 10KHz		
Outputs	Pre-Out	0dB,600 Ω unbalanced, RCA pin jack		
		0dB,600 Ω unbalanced, XLR-3-31		
	Direct Output	High Impedance:100V screw terminal		
		Low Impedance:4-16 Ω screw terminal		
Inputs	MIC 1	-30dB,600 Ω electronically-balanced, combine type of XLR-3-31 equivalent and phone jack		
	MIC 2	-30dB,600 Ω electronically-balanced, combine type of XLR-3-31 equivalent and phone jack		
	MIC 3	-30dB,600 Ω electronically-balanced, combine type of XLR-3-31 equivalent and phone jack		
	AUX 1	-20dB,10K Ω unbalanced RCA pin jack		
	AUX 2	-20dB,10K Ω unbalanced RCA pin jack		
Operating Temperature		-10 $^{\circ}$ C to +40 $^{\circ}$ C		
Color		Black		
Dimensions (W x H x D)		420X109X35		
Weight		7.8kg	8.1kg	12.6kg