

BGM430 SERIES**Product Description:**

BGM430 is a high-performance audio amplifier designed for commercial and industrial public address applications. This type has a standard mount design with rated power of 30W each line, four lines in total, to provide a wide selection for different sound system. Both balanced and unbalanced line inputs are selectable, 17.5V, 25V, 35V, 75V and 8ohm are selectable for different speaker installation matching. Complete protection includes short circuit, overload and overheat automatic protection.

Technical Specifications:

Model:	BGM430
Power Requirement:	110~125V AC or 220~230V AC, 50/60Hz
Rated Output:	4x30W
Distortion:	Less than 1% at 1kHz
Frequency Response:	50~20,000Hz (± 3 dB)
Outputs:	
○ Pre-out 1-4	0dB, 600 Ω Unbalanced, RCA pin jack
○ Line out 1-4	0dB, 600 Ω Unbalanced, RCA pin jack
○ Direct Out 1-4	High Impedance: 70V, 35V, 25V, 17.5V screw terminal Low Impedance: 8 Ω screw terminal
Inputs:	

- Input 1 Mic 1-4 3 ~ 10mV (-50 ~ -30dBV) 10kΩ balanced Phenix Input
- Input 1 Line/Tel 316mV (-10dBV) 10kΩ (optional 600Ω transformer available) balanced Phenix 1-4
- Aux 1-4 316mV (10dBV) 10kΩ Unbalanced RCA Summing Line Level


Operating Temperature: -10°C to +40°C

Color: Black

Dimensions (W*H*D): 420mm x 109mm x 357mm

Weight: 12.2kg

Connection Options:



Application:

In airports, stations, coffee shops, markets, schools, park, and other public places.