

Subwoofers – with a stand

Technical Specifications:

Model:	CW250-R806	CW250-R406	CW250-R408	CW250-R808	CW400-PR410	CW400-PR412	CW400-PR812
Drivers:	6.5"x1	6.5"x1	8"x1	8"x1	10"x2 (passive)	12"x2 (passive)	12"x2 (passive)
Frequency Response:	20Hz-200Hz	20Hz-200Hz	20Hz-200Hz	20Hz-200Hz	20Hz-200Hz	30Hz-200Hz	25Hz-200Hz
Signal to Noise Ratio	91	91	91	91	91	91	91
Rated Impedance	8Ω	4Ω	4Ω	8Ω	4Ω	4Ω	8Ω
Output Power:	150W	150W	200W	200W	400W	400W	400W
Distortion:	<1%	<1%	<1%	<1%	<1%	<1%	<1%
Input Sensitivity:	300mV	300mV	300mV	300mV	300mV	300mV	300mV
Low Pass Adjustable Frequency:	30Hz-200Hz	30Hz-200Hz	30Hz-200Hz	30Hz-200Hz	30Hz-200Hz	50Hz-150Hz	50Hz-150Hz
Phase:	0°-180°	0°-180°	0°-180°	0°-180°	0°-180°	0°-180°	0°-180°
Dimensions (WxHxD):	285 x 335 x 300mm	285 x 335 x 300m	340 x 375 x 330mm	340 x 375 x 330mm	380 x 350 x 415mm	480 x 400 x 440mm	480 x 400 x 440mm
Net Weight	15.3 kg	15.3 kg	16.4 kg	16.4 kg	23.7 kg	29.5 kg	29.5 kg
Color Finish Options:	Black Matte / Piano Black / Ebony / Black Sandalwood / Walnut						