

Subwoofers – without a platform

Technical Specifications:

Model:	CW509-R406	CW250PR408	CW250-PR808	CW400-R410	CW400R-810	CW1200-R412
Drivers:	6.5"x2	8"X2	8"x2	10"x1	10"x1	12"x1
Frequency Response:	20Hz-200Hz	20Hz-200Hz	20Hz-200Hz	20Hz-200Hz	20Hz-200Hz	20Hz-200Hz
Signal to Noise Ratio	91	91	91	91	91	91
Rated Impedance	8Ω	4Ω	4Ω	8Ω	4Ω	4Ω
Output Power:	150W	250W	250W	400W	400W	1200W
Distortion:	<1%	<1%	<1%	<1%	<1%	<1%
Input Sensitivity:	300mV	300mV	300mV	300mV	300mV	300mV
Low Pass Adjustable Frequency:	30Hz-200Hz	30Hz-200Hz	30Hz-200Hz	30Hz-200Hz	30Hz-200Hz	25Hz-200Hz
Phase:	0°-180°	0°-180°	0°-180°	0°-180°	0°-180°	0°-180°
Dimensions (WxHxD):	285 x 250 x 270mm	310 x 280 x 300m	310 x 280 x 300mm	400 x 475 x 410mm	400 x 475 x 410mm	480 x 565 x 500mm
Net Weight	12 kg	16.1 kg	16.1 kg	29.8 kg	29.8 kg	59.7 kg
Color Finish Options:	Black Matte/ Piano Black / Ebony / Black Sandalwood / Walnut					